# BUS.12000C



# 12000 LITRE BUNDED STEEL OIL TANK C/W FILL POINT CABINET



#### TANK:

The inner tank provides the required storage area, the outer tank forms the required bund with capacity for 110% of the total liquid being stored. The tank is suitable for storage of Diesel, Kerosene and certain other oils. Please check before usage.

## THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England and Wales) 2002 PPG2. BS799 pt5

## **SPECIFICATIONS:**

- 12000 litre (2640 galls) capacity
- · Low level fill point front mounted
- · Lockable cabinet swing door
- 2" fill point inside cabinet, c/w lever ball valve & non return valve
- 1 no tank to bund vent & 2" bund vent
- 1 no 1.5" bund socket
- 2 no 1.5" tank socket

- 1 no 2" tank socket
- 1 no 1" top suction c/w stand pipe
- 2 no 0.5" sockets in cabinet for probes
- Hydrostatic unitel% tank contents gauge (other gauges can be fitted £POA)
- Battery overfill alarm
- 50mm x 100mm full length bearers
- Small tin of "touch-up" paint for applying when scratches might occur during the installation process.
- Standard Colour: Holly Green

#### **DIMENSIONS:**

Length: 4100mm (inc. cabinet)

Width: 1830mm Height: 1830mm Weight: 2000kg

Cabinet: 900mm x 900mm x 450mm

