

BUS.3500

3500 LITRE BUNDED STEEL OIL TANK



TANK:

The inner tank provides the required storage area, the outer tank forms the required bund with capacity for 110% of the total liquid being stored. The tank is suitable for storage of Diesel, Kerosene and certain other oils. Please check before usage.

THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England and Wales) 2002 PPG2. BS799 pt5

SPECIFICATIONS:

- Tough Steel construction
- 3500 litres (770 galls) capacity
- 3 No. 2" top sockets (for fill, vent & spare)
- 2 No. 1 1/2" top socket (for tank & bund gauge)
- 1 No. 1" bottom outlet socket

- 1 No. 1" top suction drain socket (plugged)
- 1 No. 2" tank to bund vent
- Tank contents gauge (optional extra)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

DIMENSIONS:

Length: 2135mm
Width: 1500mm
Height: 1250mm
Weight: 550kg

 **EasyTANK**

BUNDED STEEL TANK

EQUIPMENT OPTIONS

TANK CONTENTS GAUGES:



Clock Face
GA.CG.4



Spiral Float*
GA.F2.4



Sonic Visual
GA.AP.VI



Sonic Smart
GA.AP.SM

OUTLET FILTER KITS:



Advanced
AC.TFK.A



90°
AC.TFK.90



90° Tee
AC.TFK.90T



Parallel Tee
AC.TFK.PT



Straight Tee
AC.TFK.ST



Parallel Tee 3 Gang
AC.TFK.PT.3



Parallel Tee 4 Gang
AC.TFK.PT.4

SECURITY OPTIONS:



Locking Lid
EXT.LID



Spin Secure Tank Lock
TL.020

*Model dependent

EasyTANK