

BUS.4500C

Atlantis

4500 LITRE BUNDED STEEL OIL TANK C/W FILL POINT CABINET



TANK:

The inner tank provides the required storage area, the outer tank forms the required bund with capacity for 110% of the total liquid being stored. The tank is suitable for storage of Diesel, Kerosene and certain other oils. Please check before usage.

THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England and Wales) 2002 PPG2. BS799 pt5

SPECIFICATIONS:

- Tough Steel construction
- 4500 litres (990 galls) capacity
- Lockable cabinet with swing door
- 2" fill point inside cabinet, c/w lever ball valve & non return valve
- 1 No. tank to bund vent & 2" bund vent
- 1 No. 1.5" bund socket
- 2 No. 1.5" tank socket

- 1 No. 2" tank socket
- 1 No. 1" top suction c/w stand pipe
- 2 No. 0.5" sockets in cabinet for probes
- Tank contents gauge (optional extra)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- Hydrostatic unitel contents gauge
- Battery overfill alarm
- Low level fill point - front mounted
- Bottom outlet (please specify size with order)
- 10 year warranty

DIMENSIONS:

Length:	2890mm (inc. cabinet)
Width:	1220mm
Height:	1830mm
Weight:	970kg
Cabinet:	900mm x 900mm x 450mm

EasyTANK