BUS.5800



5800 LITRE BUNDED STEEL OIL TANK



TANK:

The inner tank provides the required storage area, the outer tank forms the required bund with capacity for 110% of the total liquid being stored. The tank is suitable for storage of Diesel, Kerosene and certain other oils. Please check before usage.

THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England and Wales) 2002 PPG2. BS799 pt5

SPECIFICATIONS:

- Tough Steel construction
- 5800 litres (1275 galls) capacity
- 3 No. 2" top sockets (for fill, vent & spare)
- 1 No. 1 1/2" top socket (for tank & bund gauge)
- 1 No. 1" bottom outlet socket

- 1 No. 1" top suction drain socket (plugged)
- 1 No. 2" tank to bund vent
- Tank contents gauge (optional extra)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

DIMENSIONS:

Length: 2440mm Width: 1525mm Height: 1830mm Weight: 1050kg




BUNDED STEEL TANK



EQUIPMENT OPTIONS

TANK CONTENTS GAUGES:



GA.CG.4



GA.F2.4



Sonic Visual GA.AP.VI



Sonic Smart GA.AP.SM

OUTLET FILTER KITS:



Advanced AC.TFK.A



AC.TFK.90



90° Tee AC.TFK.90T



Parallel Tee AC.TFK.PT



Straight Tee AC.TFK.ST



Parallel Tee 3 Gang AC.TFK.PT.3



AC.TFK.PT.4

SECURITY OPTIONS:



Locking Lid EXT.LID



Spin Secure Tank Lock TL.020

*Model dependant

