## FPS.1800.30



# 1800 LITRE TRIPLE SKINNED BUNDED STEEL TANK C/W 30 MIN INTEGRAL FIREPROOFING



#### TANK:

A triple skinned bunded tank, the inner tank provides the required storage area, the second tank forms the required bund with capacity for 110% of the total liquid being stored & the third tank povides the housing for the integral fire barrier. The tank is suitable for storage of Diesel, Kerosene & certain other oils. Please check before usage.

#### THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England & Wales) 2002 PPG2. BS799 pt5

#### **DIMENSIONS:**

- Length: 1460mm
- Width: 1460mm
- Height: 1330mm
- Weight: 620kg

### RECOMMENDED BASE SIZE:

2060mm x 2060mm

#### SPECIFICATIONS:

- Tough Steel construction
- 1800 litres (400 galls) capacity
- 30 min integral fireproof barrier (non absorbent)
- 1 No. 2" top socket for fill point
- 2 no.11/2" top socket (for tank & bund)
- 1 No. 2" tank to bund vent
- 1 No. 2" bund vent
- 1 No. 1" bottom outlet socket
- 1 No. "op suction drain socket (plugged)
- Tank contents gauge (Spiral Float Gauge)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

