# FPS.2250.60



# 2250 LITRE TRIPLE SKINNED BUNDED STEEL TANK C/W 60MIN INTEGRAL FIREPROOFING



#### TANK:

A triple skinned bunded tank, the inner tank provides the required storage area, the second tank forms the required bund with capacity for 110% of the total liquid being stored & the third tank povides the housing for the integral fire barrier. The tank is suitable for storage of Diesel, Kerosene & certain other oils. Please check before usage.

#### THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England & Wales) 2002 PPG2. BS799 pt5

## **DIMENSIONS:**

Length: 2070mmWidth: 1460mmHeight: 1430mmWeight: 810kg

### RECOMMENDED BASE SIZE:

• 2670mm x 2060mm

#### SPECIFICATIONS:

- Tough Steel construction
- 2250 litres (495 galls) capacity
- 60 min integral fireproof barrier (non absorbent)
- 1 No. 2" top socket for fill point
- 2 No. 11/2" top socket (for tank & bund)
- 1 No. 2" tank to bund vent
- 1 No. 2" bund vent
- 1 No. 1" bottom outlet socket
- 1 No. 1" top suction drain socket (plugged)
- Tank contents gauge (Spiral Float Gauge)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

