

FPS.900.60

Atlantis

900 LITRE TRIPLE SKINNED BUNDED STEEL TANK C/W 60 MIN INTEGRAL FIREPROOFING



TANK:

A triple skinned banded tank, the inner tank provides the required storage area, the second tank forms the required bund with capacity for 110% of the total liquid being stored & the third tank provides the housing for the integral fire barrier. The tank is suitable for storage of Diesel, Kerosene & certain other oils. Please check before usage.

THIS TANK COMPLIES WITH:

Oil Pollution Prevention Guidelines (England & Wales) 2002 PPG2. BS799 pt5

DIMENSIONS:

- Length: 1765mm
- Width: 850mm
- Height: 1430mm
- Weight: 520kg

SPECIFICATIONS:

- Tough Steel construction
- 900 litres (200 galls) capacity
- 60 min integral fireproof barrier (non absorbent)
- 1 No. 2" top socket for fill point
- 2 No. 1 1/1" top socket (for tank & bund gauge)
- 1 No. 2" tank to bund vent
- 1 No. 2" bund vent
- 1 No. 1" bottom outlet socket
- 1 No. 1" top suction drain socket (plugged)
- Tank contents gauge (Spiral Float Gauge)
- Outlet filter kit (optional extra)
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

RECOMMENDED BASE SIZE:

- 2365mm x 1450mm

EasyTANK